




CINTA LED EXTERIOR 14.4W 5MT.



CARACTERÍSTICAS

SKU	POTENCIA	TECNOLOGÍA	COLOR T°	CANTIDAD DE LEDS	FORMATO	PROTECCIÓN	VOLTAJE	REGULA- BLE	ACCESORIOS
CLE50506012VR-GBCR	14.4W	Epistar SMD 5050 (5mm. x 5mm.)	RGB	60 LEDS x metro	Rollo 5 metros.	IP65	12V	Si	Incluye control remoto 16 colores.
CLE50506012VAM	14.4W	Epistar SMD 5050 (5mm. x 5mm.)	Amarillo	60 LEDS x metro	Rollo 5 metros.	IP65	12V	Si	No
CLE50506012VV	14.4W	Epistar SMD 5050 (5mm. x 5mm.)	Verde	60 LEDS x metro	Rollo 5 metros.	IP65	12V	Si	No
CLE50506012VA	14.4W	Epistar SMD 5050 (5mm. x 5mm.)	Azul	60 LEDS x metro	Rollo 5 metros.	IP65	12V	Si	No
CLE50506012VR	14.4W	Epistar SMD 5050 (5mm. x 5mm.)	Rojo	60 LEDS x metro	Rollo 5 metros.	IP65	12V	Si	No
CLI505012VC	14.4W	Epistar SMD 5050 (5mm. x 5mm.)	Luz Cálida 3000K	60 LEDS x metro	Rollo 5 metros.	IP65	12V	Si	No
CLE505012VF	14.4W	Epistar SMD 5050 (5mm. x 5mm.)	Luz Fría 3000K	60 LEDS x metro	Rollo 5 metros.	IP65	12V	Si	No

 A° ILUMINACIÓN
120°

 T° DE TRABAJO
-20 A 50° C

 VIDA ÚTIL
15.000 HRS

 CERTIFICADOS
CE & ROHS



✉ claudio@elights.cl 📞 +56950039803

